











# 2-Leg Bridle Slings

## Rated Capacity - Working Load Limit at DF 5:1

Class 6x19  Class 6x37  Sling Dia. Inch	Direct Hitch <sup>(1)</sup>			Choker Hitch <sup>(2)</sup>		
	 WLL tons 60°	 WLL tons 45°	 WLL tons 30°	 WLL tons 60°	 WLL tons 45°	 WLL tons 30°
1/4"	.90	.70	.53	.70	.52	.40
5/16"	1.50	1.2	.88	1.14	.90	.66
3/8"	2.2	1.8	1.3	1.65	1.3	1.0
7/16"	3.1	2.5	1.8	2.3	1.9	1.4
1/2"	4.0	3.2	2.3	3.0	2.4	1.7
9/16"	4.8	3.9	2.8	3.6	2.9	2.1
5/8"	6.0	4.9	3.5	4.5	3.7	2.6
3/4"	8.8	7.2	5.1	6.6	5.4	3.8
7/8"	11.9	9.7	6.9	8.9	7.3	5.2
1"	15.3	12.5	8.9	11.5	9.4	6.7
1-1/8"	19	15.2	11	14	11.4	8.3
1-1/4"	22	18	13	16	14	9.8
1-3/8"	27	22	16	20	17	12
1-1/2"	33	27	19	25	20	14
1-3/4"	45	37	26	34	28	20
2"	57	47	33	43	35	25

(1) All Rated Capacities are based on a D/d ratio of >25:1  
 (2) Rated Capacity are based on a D/d ratio of >25:1 and choking angle greater than 135°. ALL sling angles refer to the HORIZONTAL angle.  
 All Rated Capacities (WLL's) on multiple leg slings are based on EQUAL loading of all sling legs.

## Standard Sling Components

Sling Dia. Inch	Single Leg WLL vert. tons	Shackle Size nominal	Shackle WLL tons	Shackle Pin Dia. Inch	Eye Hook Size tons	Swivel Hook Size tons	Self Locking Hook Size nominal	Self Locking Swivel Hook Size nominal
1/4"	1.8	1/4"	.5	.31	.75 C	.75 C	6	6
5/16"	3.0	5/16"	.75	.38	1 C	1 C	6	6
3/8"	4.5	3/8"	1.0	.44	1.5 C	1.5 C	8	8
7/16"	6.2	7/16"	1.5	.50	2 C	2 C	8	8
1/2"	8.0	1/2"	2.0	.63	3 A	3 A	10	10
9/16"	9.7	5/8"	3.25	.75	3 C	3 C	13	13
5/8"	12.1	3/4"	4.75	.88	5 A	4.5 A	13	13
3/4"	17.7	7/8"	6.5	1.00	5 C	5 C	16	16
7/8"	23.9	1"	8.5	1.13	7 A	7 A	16	16
1"	30.8	1-1/8"	9.5	1.25	11 A	11 A	n/a	n/a
1-1/8"	38.1	1-1/4"	12.0	1.38	11 A	11 A	n/a	n/a
1-1/4"	45.0	1-3/8"	13.5	1.50	15 A	15 A	n/a	n/a
1-3/8"	55.4	1-1/2"	17	1.63	22 A	22 A	n/a	n/a
1-1/2"	65.8	1-3/4"	25	2.00	22 A	22 A	n/a	n/a
1-3/4"	90.1	1-3/4"	25	2.00	30 A	30 A	n/a	n/a
2"	114.3	2"	35	2.25	37 A	n/a	n/a	n/a


Follow OSHA, ANSI B30.9 and Manufacturers Guidelines. Can fail if damaged, misused or overloaded. Inspect before use. Use only if trained. Do not exceed rated capacity. Protect sling from contact with edges. DEATH or INJURY can occur from improper use or maintenance.










# 3-Leg Bridle Slings

## Rated Capacity - Working Load Limit at DF 5:1



Class 6x19  Class 6x37  Sling Dia. Inch	Direct Hitch <sup>(1)</sup>		
	 WLL tons 60°	 WLL tons 45°	 WLL tons 30°
1/4"	1.4	1.1	.80
5/16"	2.3	1.9	1.3
3/8"	3.4	2.8	1.9
7/16"	4.7	3.8	2.7
1/2"	6.0	4.9	3.4
9/16"	7.3	5.9	4.2
5/8"	9.1	7.4	5.2
3/4"	13.3	10.8	7.6
7/8"	17.9	14.6	10.3
1"	23.1	18.9	13.3
1-1/8"	28.6	23.3	16.5
1-1/4"	33.8	27.6	19.5
1-3/8"	41.6	33.9	24.0
1-1/2"	49.4	40.3	28.5
1-3/4"	67.5	55.1	39.0
2"	85.7	70.0	49.5

(1) All Rated Capacities are based on a D/d ratio of >25:1  
 ALL sling angles refer to the HORIZONTAL angle.  
 All Rated Capacities (WLL's) on multiple leg slings are based on EQUAL loading of all sling legs.

## Standard Sling Components

Sling Dia. Inch	Single Leg WLL vert. tons	Shackle Size nominal	Shackle WLL tons	Shackle Pin Dia. Inch	Eye Hook Size tons	Swivel Hook Size tons	Self Locking Hook Size nominal	Self Locking Swivel Hook Size nominal
1/4"	1.4	1/4"	.5	.31	.75 C	.75 C	6	6
5/16"	2.3	5/16"	.75	.38	1 C	1 C	6	6
3/8"	3.4	3/8"	1.0	.44	1.5 C	1.5 C	8	8
7/16"	4.7	7/16"	1.5	.50	2 C	2 C	8	8
1/2"	6.0	1/2"	2.0	.63	3 A	3 A	10	10
9/16"	7.3	5/8"	3.25	.75	3 C	3 C	13	13
5/8"	9.1	3/4"	4.75	.88	5 A	4.5 A	13	13
3/4"	13.3	7/8"	6.5	1.00	5 C	5 C	16	16
7/8"	17.9	1"	8.5	1.13	7 A	7 A	16	16
1"	23.1	1-1/8"	9.5	1.25	11 A	11 A	n/a	n/a
1-1/8"	28.6	1-1/4"	12.0	1.38	11 A	11 A	n/a	n/a
1-1/4"	33.8	1-3/8"	13.5	1.50	15 A	15 A	n/a	n/a
1-3/8"	41.6	1-1/2"	17	1.63	22 A	22 A	n/a	n/a
1-1/2"	49.4	1-3/4"	25	2.00	22 A	22 A	n/a	n/a
1-3/4"	67.5	1-3/4"	25	2.00	30 A	30 A	n/a	n/a
2"	85.7	2"	35	2.25	37 A	n/a	n/a	n/a






### WARNING


Follow OSHA, ANSI B30.9 and Manufacturers Guidelines. Can fail if damaged, misused or overloaded. Inspect before use. Use only if trained. Do not exceed rated capacity. Protect sling from contact with edges. DEATH or INJURY can occur from improper use or maintenance.



# 4-Leg Bridle Slings

## Rated Capacity - Working Load Limit at DF 5:1

Class 6x19  Class 6x37  Sling Dia. Inch	Direct Hitch <sup>(1)</sup>		
	 WLL tons 60°	 WLL tons 45°	 WLL tons 30°
1/4"	1.8	1.5	1.1
5/16"	3.0	2.5	1.8
3/8"	4.5	3.7	2.6
7/16"	6.2	5.1	3.6
1/2"	8.0	6.5	4.6
9/16"	9.7	7.9	5.6
5/8"	12.1	9.9	7.0
3/4"	17.7	14.4	10.2
7/8"	23.9	19.5	13.8
1"	30.8	25.2	17.8
1-1/8"	38.1	31.1	22.0
1-1/4"	45.0	36.8	26.0
1-3/8"	55.4	45.2	32.0
1-1/2"	65.8	53.7	38.0
1-3/4"	90.1	73.5	52.0
2"	114.3	93.3	66.0



(1) All Rated Capacities are based on a D/d ratio of >25:1  
 ALL sling angles refer to the HORIZONTAL angle.  
 All Rated Capacities (WLL's) on multiple leg slings are based on EQUAL loading of all sling legs.

## Standard Sling Components

Sling Dia. Inch	Single Leg WLL vert. tons	Shackle Size nominal	Shackle WLL tons	Shackle Pin Dia. Inch	Eye Hook Size tons	Swivel Hook Size tons	Self Locking Hook Size nominal	Self Locking Swivel Hook Size nominal
1/4"	1.8	1/4"	.5	.31	.75 C	.75 C	6	6
5/16"	3.0	5/16"	.75	.38	1 C	1 C	6	6
3/8"	4.5	3/8"	1.0	.44	1.5 C	1.5 C	8	8
7/16"	6.2	7/16"	1.5	.50	2 C	2 C	8	8
1/2"	8.0	1/2"	2.0	.63	3 A	3 A	10	10
9/16"	9.7	5/8"	3.25	.75	3 C	3 C	13	13
5/8"	12.1	3/4"	4.75	.88	5 A	4.5 A	13	13
3/4"	17.7	7/8"	6.5	1.00	5 C	5 C	16	16
7/8"	23.9	1"	8.5	1.13	7 A	7 A	16	16
1"	30.8	1-1/8"	9.5	1.25	11 A	11 A	n/a	n/a
1-1/8"	38.1	1-1/4"	12.0	1.38	11 A	11 A	n/a	n/a
1-1/4"	45.0	1-3/8"	13.5	1.50	15 A	15 A	n/a	n/a
1-3/8"	55.4	1-1/2"	17	1.63	22 A	22 A	n/a	n/a
1-1/2"	65.8	1-3/4"	25	2.00	22 A	22 A	n/a	n/a
1-3/4"	90.1	1-3/4"	25	2.00	30 A	30 A	n/a	n/a
2"	114.3	2"	35	2.25	37 A	n/a	n/a	n/a

Follow OSHA, ANSI B30.9 and Manufacturers Guidelines. Can fail if damaged, misused or overloaded. Inspect before use. Use only if trained. Do not exceed rated capacity. Protect sling from contact with edges. DEATH or INJURY can occur from improper use or maintenance.

