





# Tie-Down Systems

**2" Tie-Downs** (Polyester Webbing)  
complete with Ratchet and End Fittings as shown.  
Standard Length is 20 ft (2 ft Tail, 18 ft Strap)

Rated Capacity 3,300 lbs

All Tie Down systems come with a sturdy vinyl Capacity Tag stating safety precautions and load ratings at various tie-down angles. Tag firmly sewn to strap (no flag).



## Description



Flat Hooks at both ends



5/16" Grade 7 Chain Assembly at both ends (12" chain length)




1/2" Narrow Wire Hook at both ends



Delta Ring at both ends



Loop Splice at both ends



Endless

## 2" Tie-Down Replacement Straps




Flat Hooks at one end




5/16" Grade 7 Chain Assembly at one end (12" chain length)



1/2" Narrow Wire Hook at one end



Delta Ring at one end



Loop Splice at one end




# Tie-Down Systems

**3" Tie-Downs** (Polyester Webbing)  
complete with Ratchet and End Fittings as shown.  
Standard Length is 20 ft (2 ft Tail, 18 ft Strap)

Rated Capacity: See below

All Tie Down systems come with a sturdy vinyl Capacity Tag stating safety precautions and load ratings at various tie-down angles. Tag firmly sewn to strap (no flag).



## Description



Flat Hooks at both ends



5/16" Grade 7 Chain Assembly at both ends (12" chain length)



Delta Ring at both ends



5/8" Narrow Hook at both ends



Loop Splice at both ends



Endless

## 3" Tie Down Replacement Straps




Flat Hooks at one end




5/16" Grade 7 Chain Assembly at one end (12" chain length)



Delta Ring at one end



5/8" Narrow Hook at one end



Loop Splice at one end

