



# *Twin-Path® Eye and Eye Sling*

---

## **TWIN-PATH® EYE & EYE SYNTHETIC SLING**

US Patent #5,727,833 & #4,850,629



**EE** This product is made to be an eye and eye sling only. Usually an eye and eye sling is made from a round sling with a sleeve over it to form the eyes at each end. This sling is light, strong and less

expensive than a round sling with a sleeve. It can be manufactured using either K-Spec® core yarn or polyester. Riggers have told us that they have some applications where they want an eye and eye sling only and this is the one with all of the Twin-Path® features in a strictly eye and eye product. Order by model number and length i.e. TPXCEE 2,000 x 10'.



# Twin-Path® Eye and Eye Sling

## TWIN-PATH® EYE & EYE SYNTHETIC SLING

US Patent #5,727,833 & #4,850,629

**EE** This product is made to be an eye and eye sling only. Usually an eye and eye sling is made from a round sling with a sleeve over it to form the eyes at each end. This sling is light, strong and less expensive than a round sling with a sleeve. It can be manufactured using either K-Spec® core yarn or polyester. Riggers have told us that they have some applications where they want an eye and eye sling only and this is the one with all of the Twin-Path® features in a strictly eye and eye product.



## TWIN-PATH® EYE AND EYE SLING

STOCK NUMBERS	CHOKER	VERTICAL	BASKET 60°	VERTICAL BASKET	WT. LBS. PER FT.	WIDTH when flat
TPXCEE 1,000	8,000	10,000	17,320	20,000	.28	3"
TPXCEE 1,500	12,000	15,000	25,980	30,000	.36	3"
TPXCEE 2,000	16,000	20,000	34,600	40,000	.50	4"
TPXCEE 2,500	20,000	25,000	43,300	50,000	.60	5"
TPXCEE 3,000	24,000	30,000	52,000	60,000	.75	5"
TPXCEE 4,000	32,000	40,000	69,200	80,000	1.00	6"
TPXCEE 5,000	40,000	50,000	86,500	100,000	1.40	6"

Sling can fail if damaged, misused or overloaded. Inspect before use. Damaged sling shall not be used. Use only if trained. Do not exceed rated capacity. Protect sling from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali, sunlight and temperature over 180°F. DEATH or INJURY can occur from improper use or maintenance.

**⚠ WARNING**