



# Check-Fast® High Performance Roundslings

US Patent #7,661,737 CA #2,547,632 EP #1899255

This is the only single-path, high performance fiber roundsliding with an overload indicator. The Covermax® is the most durable available for a synthetic sling. Also available in polyester - SPCF slings up to SPCF 6000, 60,000 lb. vertical.

SINGLE-PATH EXTRA COVERMAX® WITH CHECK-FAST® INSPECTION							
Single-Path K-Spec ® Slings Stock No.	Rated Capacities (lbs.)					Approx. Weight (lbs. per Ft.) (Bearing- Bearing)	Nominal Body Width (inches)
	Vertical	Choker	Vertical Basket	Basket Hitches			
			90°	60°	45°		
SPXCF 500	5000	4000	10000	8660	7070	0.34	2.5"
SPXCF 1000	10000	8000	20000	17320	14140	0.38	2.5"
SPXCF 1500	15000	12000	30000	25980	21210	0.44	2.5"
SPXCF 2000	20000	16000	40000	34640	28280	0.52	2.5"
SPXCF 2500	25000	20000	50000	43300	35350	0.59	3"
SPXCF 3000	30000	24000	60000	51960	42420	0.65	3"
SPXCF 4000	40000	32000	80000	69280	56560	0.85	3"
SPXCF 5000	50000	40000	100000	86600	70700	0.98	4"
SPXCF 6000	60000	48000	120000	103920	84840	1.11	4"
SPXCF 7000	70000	56000	140000	121240	98980	1.24	4"
SPXCF 8500	85000	68000	170000	147220	120190	1.63	5"
SPXCF 10000	100000	80000	200000	173200	141400	1.81	5"

**METRIC CAPACITIES AVAILABLE**

**DO NOT EXCEED RATED CAPACITY**

## WARNING!

Slings can fail if damaged, misused or overloaded. Inspect before use. Damaged sling shall not be used. Use only if trained. Do not exceed rated capacity. Protect slings from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali and temperature over 300°F. DEATH or INJURY can occur from improper use or maintenance.