



Sparkeater®

When you have a hot environment up to 300°F (149°C), use a Sparkeater ® to lift the load without marring the surface of the lifted piece. Also, when doing stage rigging, order this product with a black cover for the protection it gives from exposure to fire, heat, sparks and pyrotechnics. These slings are made from aramid high performance core yarns and an aramid cover. The Offshore Certification Bureau identified these slings as good as wire rope or chain for use in offshore applications in the oil industry. As with all Twin-Path ® slings, an inner red cover provides an early warning safety alert.

SPARKEATER							
Twin-Path Stock No.	Rated Capacities (lbs.)					Approx. Weight (lbs. per Ft.) (Bearing-Bearing)	Nominal Body Width (inches)
	Vertical	Choker	Vertical Basket	Basket Hitches			
			90°	60°	45°		
TPSE 1000	10000	8000	20000	17320	14140	0.4	1.5 - 3"
TPSE 1500	15000	12000	30000	25980	21210	0.45	1.5 - 3"
TPSE 2000	20000	16000	40000	34640	28280	0.51	1.5 - 3"
TPSE 2500	25000	20000	50000	43300	35350	0.57	1.5 - 3"
TPSE 3000	30000	24000	60000	51960	42420	0.71	2.0 - 4"
TPSE 4000	40000	32000	80000	69280	56560	0.83	2.0 - 4"
TPSE 5000	50000	40000	100000	86600	70700	1.14	2.0 - 4"
TPSE 6000	60000	48000	120000	103920	84840	1.27	2.0 - 4"
TPSE 7000	70000	56000	140000	121240	98980	1.39	3.5 - 7"
TPSE 8500	85000	68000	170000	147220	120190	1.65	3.5 - 7"
TPSE 10000	100000	80000	200000	173200	141400	1.84	3.5 - 7"

METRIC CAPACITIES AVAILABLE

DO NOT EXCEED RATED CAPACITY

PLEASE NOTE: CAPACITIES SHOWN INCLUDE BOTH PATHS AND ARE FOR ONE COMPLETE SLING. SMALLER AND LARGER CAPACITIES AVAILABLE UPON REQUEST.

WARNING!

Slings can fail if damaged, misused or overloaded. Inspect before use. Damaged sling shall not be used. Use only if trained. Do not exceed rated capacity. Protect slings from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali and temperature over 300°F. DEATH or INJURY can occur from improper use or maintenance.