



Twin-Path ® Eye & Eye Synthetic Sling

US Patent #5,651,572 CA #2,195,393 EP #0785163 Japan #2929431 Australia #707924

Riggers have told us that they have some applications where they want an eye and eye sling only and this is the one with all of the TWIN-PATH ® features in a strictly eye and eye product. It is a single-bodied sling with integrated eyes.

TWIN-PATH ® EYE & EYE SLING (Capacities in lbs.)						
STOCK NUMBERS	CHOKER	VERTICAL	BASKET 60°	VERTICAL BASKET	WT. (lbs.) per/Ft.	NOMINAL WIDTH
TPXCEE 1,000	8000	10000	17320	20000	0.28	3"
TPXCEE 1,500	12000	15000	25980	30000	0.36	3"
TPXCEE 2,000	16000	20000	36640	40000	0.5	3"
TPXCEE 2,500	20000	25000	43300	50000	0.6	4"
TPXCEE 3,000	24000	30000	52000	60000	0.75	4"
TPXCEE 4,000	32000	40000	69280	80000	1	4"
TPXCEE 5,000	40000	50000	86200	100000	1.4	5"

WARNING!

Slings can fail if damaged, misused or overloaded. Inspect before use. Damaged sling shall not be used. Use only if trained. Do not exceed rated capacity. Protect slings from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali and temperature over 180°F. DEATH or INJURY can occur from improper use or maintenance.