


Hand Splice Sling



HAND TUCKED SPLICE

Fiber Core

Vertical, Choker or Vertical Basket

Rated capacity in tons of 2,000 lbs
 Rated capacity shown apply only to 6 x19 and 6 x 36 classification wire rope

Rope Dia. (Inches)	Vertical		Choker		Vertical Basket	
	EIPS	EEIPS	EIPS	EEIPS	EIPS	EEIPS
1/4	0.49	0.60	0.42	0.46	1.1	1.2
5/16	0.76	0.92	0.66	0.72	1.7	1.8
3/8	1.1	1.3	0.94	1.0	2.4	2.6
7/16	1.4	1.7	1.3	1.4	3.2	3.5
1/2	1.8	2.2	1.6	1.8	4.0	4.5
9/16	2.3	2.8	2.1	2.3	5.0	5.6
5/8	2.8	3.4	2.6	2.8	6.2	6.8
3/4	3.9	4.7	3.7	4.0	8.6	9.4
7/8	5.2	6.2	5.0	5.5	11	12
1	6.7	8.1	6.4	7.1	15	16
1 - 1/8	8.4	10	8.1	8.9	19	20
1 - 1/4	10	13	9.9	11	23	25
1 - 3/8	12	15	12	13	27	30
1 - 1/2	15	18	14	16	32	36
1 - 5/8	17	21	16	18	38	41
1 - 3/4	20	24	19	21	44	48
1 - 7/8	23	27	22	24	50	55
2	26	31	25	27	56	62
2 - 1/8	29	35	28	30	63	69
2 - 1/4	32	39	31	34	70	77
2 - 3/8	36	43	34	38	78	86
2 - 1/2	39	47	38	41	86	94

RATED CAPACITIES BASKET HITCH BASED ON D/d RATION OF 25
 RATED CAPACITIES BASED ON PIN DIAMETER NO LARGER THAN NATURAL EYE WIDTH
 OR THAN THE NOMINAL SLING DIAMETER
 RATED CAPACITIES BASED ON DESIGN FACTOR OF 5
 HORIZONTAL SLING ANGLES LESS THAN 30 DEGREES SHALL NOT BE USED